



Introduction to HYBUILD

G. Zsembinszki, A. Frazzica, V. Palomba, J. Emhofer, T. Barz, L. F. Cabeza University of Lleida, CNR ITAE, AIT

HYBUILD

INNOVATIVE COMPACT HYBRID ELECTRICAL/THERMAL STORAGE SYSTEM FOR LOW ENERGY BUILDINGS

Sustainable Places 2020 Integrated Storage systems for Residential buildings Workshop 29 October 2020 Digital Event







0 Outline

- 1. HYBUILD in a nutshell
- 2. Overall concept
- 3. Implementation
- 4. Innovation in HYBUILD
- 5. Critical aspect in the implementation
- 6. Conclusions







HYBUILD in a nutshell

- Project start: **10/2017**

Project end: 03/2022

Overall EU contribution: 5,995,840 €

Consortium: 20 partners, 9 countries

Coordinator: COMSA



Kick-off meeting Brussels - 10/2017











































www.hybuild.eu







1 HYBUILD in a nutshell

- HYBUILD aims to develop two innovative hybrid storage concepts
 - 1. For Mediterranean climate primarily for cooling energy supply
 - 2. For Continental climate primarily meant for heating and DHW supply
- The concepts are based on innovative components such as:
 - a compact sorption module
 - a high-density latent storage
 - a reversible vapour compression heat pump
 - a DC-bus interconnection
- The whole systems will be properly managed by advanced controls and Building Energy Management Systems (BEMS)
- The systems will be validated in three different demo-sites






HYBUILD in a nutshell





Overall concept


Mediterranean system (cooling)





Overall concept

Continental system (heating & DHW)







1st year

KPIs definition and first modules modelling and design





3rd year

Control development and preintervention one-year demosites monitoring



Full-year demosites monitoring and system model validation for replicability analysis

4th & 1/2 year











TRL 5















Installation of the integrated storages in the demo-sites and start monitoring
















Continental system



Mediterranean system











Innovation in HYBUILD

From the EEB-06-2017 call:

... hybrid approaches encompass different aspects, which may be addressed separately or coherently:

- high efficiency conversion and storage of surplus renewable electricity into heat;
- multifunctional use in both heating and cooling applications at different temperature grades;
- different time scales, e.g. in seasonal storage of high temperature solar heat and peak-shaving in lower temperature heat—pump applications.







Innovation in HYBUILD

high efficiency conversion and storage of surplus renewable electricity into heat:

- System based on reversible heat pumps to convert electricity into energy for heating/cooling or DHW;
- Innovation @ heat pump level fully integrated with the sorption and latent storage.



Integrated hybrid sorption/vapour compression chiller



Modular integrated PCM/water/refrigerant storage









Innovation in HYBUILD

multifunctional use in both heating and cooling applications at different temperature grades:

- Two systems specifically optimized for cooling and heating season;
- Mediterranean concept able to increase the electric COP of the chiller thanks to the sorption storage;
- Continental concept able to recover and store energy from super-heated gas out from the compressor to provide DHW, increasing the overall COP.









Innovation in HYBUILD

different time scales, e.g. in seasonal storage of high temperature solar heat and peak-shaving in lower temperature heat—pump applications:

- Possibility to operate the sorption module both as short-term or longterm storage;
- Latent storages to increase flexibility in operation and efficiency of the heat pumps on daily basis;
- Electrical storages to further increase the flexibility and selfconsumption of the system.





Critical aspect in the implementation

Integration of the heat pump & sorption chiller & latent storage

Overall system control logic definition and implementation

Continuous one full-year post-intervention monitoring at demo sites





6 Conclusions

- HYBUILD project will develop innovative fully-integrated components for hybrid electric/thermal storage solutions at domestic level
- The developed solutions will be optimized for both heating and cooling applications. Three demo sites will be employed to validate the solutions
- The lab-scale systems have been completed and their testing under labcontrolled conditions is performed
- A clear critical aspect is represented by the overall system control implementation at the demo sites





THANK YOU



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 768824





