

Renovation process challenges and barriers: Developing an information exchange framework to address the communication and coordination bottlenecks in the zero-energy renovation process.



Thaleia Konstantinou, Alejandro Prieto, Tatiana Armijos Architectural Façades & Products (AF&P) Research Group TU Delft / Faculty of Architecture and The Built Environment

> picture source: Energiesprong International, 2019) https://www.flickr.com/photos/150184035@N07/albums/72157690034665123). Licensed under CC BY 2.0






This project has received funding from the European Union's Horizon 2020 research and innovation programme under Grant Agreement n° 958445


TUDEIft Delft University of Technology

Refurbishment potential

- The building sector biggest energy user.
- Residential and service buildings 36% of energy consumption in EU
- Both rate and depth need to increase
- Deep Renovation to Zero-energy building



http://renovate-europe.eu/the-campaign/ambition-objectives/



Deep renovation

Final energy saving (% reduction)


0-30%

30-60%

60-90%

90%

- Minor
- Modarate
- Deep
- nZEB



Deep renovation path



source: BPIE. (2011). Europe's buildings under the microscope.

Industrialised Retrofits


- Improving the productivity to make upscaling possible.
- Cost reduction through economy of scales.
- Reduced on-site construction time and disturbance for occupants
- Design and engineering efficiency
- Reduction of construction waste and material use.





Stromversnelling, Soesterberg

Barriers to renovation





Barriers to renovation identified by the BPIE survey "European buildings under the microscope.

Figure from: BPIE, 2011

Objective



- Map the renovation process
- Address the most important **bottlenecks**
- Make the renovation process more efficient
- Identify the type of information that the stakeholders require during the different renovation phases
- Structure the **workflow** between all the actors.

Methods

(1) Exploration of the current renovation workflow

State of the art and existing projects analysis

17 R&I EU projects, CORDIS (European Commission).


(2) Analysis of the Experts' interaction Online questionnaire




Stakeholders' workshop

TARGET USERS Hit2Gap BIM4Ren Built2Spec ARCHITECTS / ENG.CONSULTANTS **Energy Matching** Design support tool BERTIM **BUILDING CONTRACTORS EUReCA** platform Risk limitation / efficient use of resources **One Click LCA Platform COMPONENT/SYSTEMS SUPPLIERS** StepUP Warranties / How products can be integrated/applied? NewTREND Retrokit **ENERGY SOLUTION PROVIDERS** BRESAER Energy savings estimation Zero-Plus **BUILDING MANAGERS/USERS** BERTIM Data for efficient operation over time HEAT4COOL **BUILDING OWNERS/INVESTORS** BASAJAUN Return of the investment in the short/long term SunHorizon GOVERNMENT BODIES RenoZEB Information for policy making and implementation BIPVBOOST

The sample: Core business of the organisations?



The sample: Core business of the organisations?





Results




The main questions of the study:

- Renovation process: phases, tasks
- Stakeholder per phase and their role
- Information flow
- Main perceived bottlenecks



1. Renovation process

- Pre-project: defines the need for the project, the problems, the ambition. Setup the design team
- Pre-construction: develops appropriate design solution
- Construction: Apply the solution. Manufacturing, assembly off-site and on site
- Post-construction: monitoring and maintenance of the project.




Stakeholders' involvement per phase

- Main stakeholders' involvement per phase (low / medium / high perceived involvement)
- Design team is heavily involved in phases 1-4.
- Construction team present in phases 3-4.
- Energy solution providers are seen involved throughout the process, but mostly in 3 & 4.
- Client team involved throughout the process but mostly in phase 1 (users, managers & owners also heavily involved in phases 4 & 5).



Stakeholder	PHASE 1	PHASE 2	PHASE 3	PHASE 4	PHASE 5
Architects					
Engineering consultants					
Contractors					
System suppliers					
Energy solution providers					
Building users & managers					
Building owners					
Developers / investors					
Government bodies					

Specific info per phase: Required INPUTS




Specific info per phase: INPUTS overview

*Low/medium/high relative mentions per phase are shown with colours (the darker the colour, the highest the number of mentions per phase).



Input	PHASE 1	PHASE 2	PHASE 3	PHASE 4	PHASE 5
Description of the existing building					
Pictures from the building and services					
2D plans and/or 3D models of the building					
Description of building services					
Properties of the envelope and its components					
Building retrofitting scenarios					
Monitoring data from on-site sensors					
Energy consumption information					
Weather and location data					
User schedules					
Data from occupant's questionnaires					
Cost information of components and systems					

Specific info per phase: Main OUTPUTS



Specific info per phase: OUTPUTS overview

*Low/medium/high relative mentions per phase are shown with colours (the darker the colour, the highest the number of mentions per phase).



Output	PHASE 1	PHASE 2	PHASE 3	PHASE 4	PHASE 5
BIM/3D models					
Envelope retrofitting design scenarios					
Energy demands / consumption data					
On-site energy generation data					
Indoor comfort data					
Cost, budget and/or cash-flow info					
Quality check reports					
Data for maintenance and BMS					
LCA and LCCA					
Greenhouse Gas Emissions and/or GWP data					
Installation & Assembly guidelines					
Logistics & planning guidelines					



3.

Main perceived bottlenecks per renovation phase

Relevant bottlenecks: Renovation process

• Word cloud of all responses






Relevant bottlenecks: Renovation process

- Main types of bottlenecks identified from the responses
- LACK OF INFORMATION
- O UNCLEAR DEFINITIONS
- O NORMATIVE & COMPLIANCE
- **O** COORDINATION & COMMUNICATION
- o RESPONSIBILITES & GUARANTEES
- O UNRELIABLE ASSESSMENTS
- TECHNICAL CHALLENGES
- o OTHERS

ENSNARE

Identified types of bottlenecks



Relevant bottlenecks: General overview

*Darker colours						
represent a higher						
amount of mentions						
per bottleneck type.						

	LACK OF INFORMATION	UNCLEAR DEFINITIONS	NORMATIVE & COMPLIANCE	COORDINATION & COMMUNICATION	RESPONSIBILITES & GUARANTEES	UNRELIABLE ASSESSMENTS	TECHNICAL CHALLENGES	OTHERS
PHASE 1	building (construction, re envelope, structure). - Limited energy consumption th	nclear definition of the novation objective and KPIs. nclear design proposals at s stage hinder the clients' cision-making process.	- Bureaucracy	- Limited involvement and participation of specialists - (mostly developer and owner).		 Not enough depth in the technical project to come up with reliable cost estimations. 	-	- Lack of interested clients and governmental incentives.
PHASE 2	Limited info about the existing building and its use. Not enough technical information about building products. Limited availability of project information (drawings & specifications).		- Bureaucracy - Unclear overview of Natii or local normatives that ne be followed.	- Unclear client-designer	Unclear responsibilities of the cal architects and other akeholders.	Unreliable assessment and optimisation of different design options. Uncertain building energy performance predictions. Unreliable cost predictions of energy services.	-	- Lack of skilled professionals to assemble a consortium.
PHASE 3		nclear technical solutions d installation techniques for dget calculations and ocurement.	- Approval of the project b local authorities.		Jnclear responsibilities and bilities at the procurement age for quality checks, livery, defects and placements during and after nstruction.	-	 Integration and fine tunning or all the elements and components. 	f - Lack of skilled professionals to assemble a consortium.
PHASE 4	- Not always enough technical information about the renovation components (façade panels)		- Permits and green light fr the local authorities and th client.	 On and off-site logistics and work-flow. Unclear communication channels between stakeholders - and coordination issues between the supply-chain and contractors. Unclear communication with owners and users. 	sponsibilities between	-	- Design and maintenance of the envelope. - Errors in accuracy might jeopardize the installation on- site. - Lack of standardisation.	
PHASE 5	Post-occupancy evaluation is still rarely performed. Limited access to monitoring data, which is usually fragmented. Limited info on users' scheduled.		-					- Lack of incentives for landlords in tenant-based scenarios.



Relevant bottlenecks: Main takeaways

- Lack of information seems to be the main perceived bottleneck during phase 1 (preproject) and phase 2 (concept design).
- **Coordination and communication** between different stakeholders is the main perceived bottleneck type at phase 4 (execution and handover), along with **technical challenges**.
- Unreliable assessments were mentioned as a relevant bottleneck during Concept design (phase 2).



Conclusion



- To increase rate of renovation we need to make the process more **efficient**
- Stakeholders' communication and information exchange need to improve
- Understand the **process**, which parties and what information is crucial

Recommendations



- Archetypes, to provide scenarios and indication of cost and energy at the early stage, with minimum effort
- Comprehensive **building data** checklist, considering the level of detail for said information at every step of the process
- Technical information on **products**, in form of catalogue.
- Construction and **suppliers** involve earlier in the process
- Clearly defined **responsibilities** of all stakeholders throughout the process
- **Communication** channels and **protocols** between the design team and the client team, for solutions approval and execution







ABUD

Advanced Building

BIONOVA

Oobatek

INEF4 🏁

& Urban Design

PCiviESCO









THANK YOU

This document and all information contained herein is the sole property of the ENSNARE Consortium or the company referred to in the slides. It may contain information subject to Intellectual Property Rights. No Intellectual Property Rights are granted by the delivery of this document or the disclosure of its content. Reproduction or circulation of this document to any third party is prohibited without the written consent of the author(s). The statements made here in do not necessarily have the consent or agreement of the ENSNARE Consortium and represent the opinion and findings of the author(s). The dissemination and confidentiality rules as defined in the Consortium Agreement apply to this document. All rights reserved.



















